

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **06196518 A**

(43) Date of publication of application: **15.07.94**

(51) Int. Cl.

**H01L 21/60**

(21) Application number: **04342419**

(22) Date of filing: **22.12.92**

(71) Applicant: **RYODEN SEMICONDUCTOR SYST  
ENG KK MITSUBISHI ELECTRIC  
CORP**


(72) Inventor: **ITO KOJI  
TOBIMATSU HIROSHI  
MOCHIZUKI HIROSHI**

**(54) SEMICONDUCTOR DEVICE**

**(57) Abstract:**

**PURPOSE:** To obtain an LOC type semiconductor device which does not damage the inside of a semiconductor element at the time of wire bonding.

**CONSTITUTION:** As to a semiconductor device wherein leads 2 are arranged above a semiconductor element 1, a shock absorber 14 relieving shock to be applied from the leads 2 at the time of wire bonding is formed at least at the parts on a surface protecting film 13 of the semiconductor element 1 with which parts the leads 2 come into contact. When the leads 2 are made to sag by wire bonding and impulsive force is applied to the semiconductor element 1, the impulsive force is transmitted to the inside of the semiconductor element 1 in the state that the impulsive force is relieved by a shock absorber 14. Hence damage is not generated in the inside of the semiconductor element 1.



**COPYRIGHT: (C)1994,JPO&Japio**